

Figure: 30 TAC §17.17(c)(1)

$$\frac{(\text{Production Capacity Factor} \times \text{Capital Cost New}) - \text{Capital Cost Old} - \text{NPVMP}}{\text{Capital Cost New}} \times 100$$

Where:

¹ **The Production Capacity Factor (PCF)** is calculated by dividing the capacity of the existing equipment or process by the capacity of the new equipment or process. When there is an increase in production capacity, PCF is used to adjust the capacity of the new equipment or process to the capacity of the existing equipment or process. When there is a decrease in production capacity, PCF is used to adjust the capacity of the existing equipment or process to the production capacity of the new equipment or process. In this case, this calculation is modified so that PCF is applied to Capital Cost Old (CCO) rather than Capital Cost New.

² **Capital Cost New** is the estimated total capital cost of the new equipment or process.

³ **Capital Cost Old** is the cost of comparable equipment or process without the pollution control. The standards used for calculating CCO are as follows:

^{3.1} If comparable equipment without the pollution control feature is on the market in the United States, then an average market price of the most recent generation of technology must be used.

^{3.2} If the conditions in variable 3.1 do not apply and the company is replacing an existing unit that already has received a positive use determination, the company shall use the CCO from the application for the previous use determination.

^{3.3} If the conditions in variable 3.1 and 3.2 do not apply and the company is replacing an existing unit, then the company shall convert the original cost of the unit to today's dollars by using a published industry specific standard. If the production capacity of the new equipment or process is lower than the production capacity of the old equipment or process CCO is divided by the PCF to adjust CCO to reflect the same capacity as CCN.

^{3.4} If the conditions in variables 3.1, 3.2 and 3.3 do not apply, and the company can obtain an estimate of the cost to manufacture the alternative equipment without the pollution control feature, then an average estimated cost to manufacture the unit must be used. The comparable unit must be the most recent generation of technology. A copy of the estimate must be provided with the worksheet including the specific source of the information.

⁴ **NPVMP**--The net present value of the marketable product recovered for the expected lifetime of the property, calculated using the equation in paragraph (2) of this subsection. Typically, the most recent three-year average price of the material as sold on the open market should be used in the calculation. If the price varies from state-to-state, the applicant shall calculate an average, and explain how the figures were determined.