

Figure: 30 TAC §217.53(d)(3)

**Table C.1.**

<b>Case</b>	<b>Protection Requirement</b>
Parallel pipes within nine feet, where the collection system pipe is above the water supply pipe	Encased in a casing pipe according to paragraph (4) of this subsection
Crossing pipes within nine feet, where the collection system pipe is above the water supply pipe	Encased in a casing pipe according to paragraph (5)(A) of this subsection <b>-or-</b> Constructed using 150 per square inch (psi) pressure class pipe according to paragraph (5)(B) of this subsection
Parallel pipes within nine feet, where the collection system pipe is below the water supply pipe	Constructed using 150 psi pressure class pipe according to paragraph (6)(A) of this subsection <b>-or-</b> Encased in a casing pipe according to paragraph (6)(B) of this subsection
Crossing pipes within nine feet, where the collection system pipe is below the water supply pipe	Constructed using 150 psi pressure class pipe according to paragraph (7)(A) of this subsection <b>-or-</b> Encased in cement-stabilized sand according to paragraph (7)(B) of this subsection <b>-or-</b> Encased in a casing pipe according to paragraph (7)(C) of this subsection
Manhole within nine feet of a water supply pipe	No measurable leakage according to paragraph (8)(A) of this subsection <b>-or-</b> Encased in cement-stabilized sand according to paragraph (8)(B) of this subsection